



THERMACELS™

Insulating Ceramic Additive for paint

DIRECTIONS FOR USE

The additive should be gradually stirred into the appropriate size container of paint.

One Pre-measured 1 gallon package of ThermaCels Ceramic Additive for one gallon of paint or a Pre-measured 5 gallon package of ThermaCels Ceramic Additive for a 5 gallon pail of paint.
(Mixing ratio is 4 parts paint to 1 part Ceramic Additive)

If you purchased a bulk contractor package, simply measure out a 1 qt container (32 oz. vol.) or use a kitchen measuring cup (4 cups = 1 QT of ThermaCels for each one gallon of paint).

DO NOT try to mix this package directly into your container of paint as it will not all fit. Get a second or larger container to use for mixing purposes. Simply pour your paint into the larger sized container and mix in the Ceramic Additive while stirring slowly to avoid clumping of the additive. Make sure to completely mix all of the Ceramic Additive into your paint! Always stir your paint for a minute or two prior to commencing painting if the paint has been sitting for more than 2 hours since last used.

Note: Recommended Roller Size 1/2" to 3/4" nap depending on surface texture..

Spraying: Remove all filters Tip Size .019 - .024 or larger depending on viscosity of paint.

The ThermaCels will leave a mild texture (suede look) to the surface to which it has been applied which will help hide defects in a wall surface.

We require 2 coats of paint containing the insulating ceramics to insure complete, uniform distribution of the insulating "beads."

NOTE: If needed add up to 1 pint of water per gallon of paint or reduce with Hy-Tech Acri-Flow to help the paint to flow better!

SAFETY DATA: Hy-Tech Ceramic Additive is a very environmentally friendly blend of organic ceramic microspheres which are non-toxic. Inhalation of large amounts of this product in its free powdered state could cause respiratory irritation and a dust mask should be worn if working around large airborne concentrations of this product prior to mixing with paint. If eye irritation occurs, flush eyes with water and if problems persist consult a physician.

Hy-Tech Thermal Solutions

159 Parkhill Blvd.

Melbourne, FL 32904

www.hytechsales.com

Toll Free 1-866-649-8324



Like us on
Facebook